

Product data sheet

610 087 3

Ferrule crimping tool PEW 8.87

Front and sideways insertion



- For crimping insulated and non-insulated ferrules according to DIN 46 228
- Self-adjusting adaptation to the required size of ferrule
- Easiest to work with when working conditions are cramped
- Square crimp profile with 4 profiled crimp surfaces
- Precise, factory-set (calibrated) crimping pressure, can be re-adjusted
- Force magnified by lever action to ensure fatigue-free working
- Consistent crimping quality with forced-lock completion of crimping process (can be released)
- Specially hardened spring steel
- Front insertion up to max. 10.0 mm² possible
- Sideways insertion up to max. 2.5 mm² possible

General

Article Number	610 087 3
EAN	4049002016417
Weight	520 g
Dimension	194 x 78 x 24 mm
Dimension packaging	244 x 78 x 26 mm

Specifications

Finish	black-oxide finish
Grips	2-component grips
Range of applications	Ferrules
Capacity	0.08 – 10.0 mm ² / AWG 28 – 8
Twin ferrules	2x 0.25 – 4.0 mm ² / 2x AWG 22 – 10

Classification

eCl@ss 10.1	ACD215012
ETIM 7.0	EC000168
proficl@ss 7.0	AAA946c003

With reservations regarding technical modifications and errors. Illustration may vary.