

Product data sheet

610 088 3

Ferrule crimping tool PEW 8.88

Front insertion



- For crimping insulated and non-insulated ferrules according to DIN 46 228
- Self-adjusting adaptation to the required size of ferrule
- Easiest to work with when working conditions are cramped
- Square crimp profile with 4 profiled crimp surfaces
- Precise, factory-set (calibrated) crimping pressure, can be re-adjusted
- Force magnified by lever action to ensure fatigue-free working
- Consistent crimping quality with forced-lock completion of crimping process (can be released)
- Specially hardened spring steel
- Huge range of applications supported in one tool (model PEW 8.88)
- Front insertion up to max. 16 mm² – useful for short conductor ends

General

Article Number	610 088 3
EAN	4049002022814
Weight	520 g
Dimension	194 x 77 x 24 mm
Dimension packaging	244 x 78 x 26 mm

Specifications

Finish	black-oxide finish
Grips	2-component grips
Range of applications	Ferrules
Capacity	0.08 – 16.0 mm ² / AWG 28 – 6
Twin ferrules	2x 0.25 – 6.0 mm ² / 2x AWG 22 – 8

Classification

eCl@ss 10.1	ACD215012
ETIM 7.0	EC000168
proficl@ss 7.0	AAA946c003

With reservations regarding technical modifications and errors. Illustration may vary.